




| FLOODED | MODEL | BCI | 20 HR | CCA @ -18°C (0°F) | MCA @ 0°C (32°F) | DIMENSIONS | WEIGHT |
|-------------|------------------|------|-------|----------------------|---------------------|-----------------------------|----------|
| 2 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S2 LI6 | LI6 | 1169 | 2729 | 3411 | 31.8 cm x 18.1 cm x 43.2 cm | 54.5 kg |
| SERIES 4000 | S2 LI6-HC | LI6 | 1335 | 3119 | 3898 | 31.8 cm x 18.1 cm x 43.2 cm | 57.5 kg |
| SERIES 4000 | S2 LI6-SC | LI6 | 1503 | 3378 | 4223 | 31.8 cm x 18.1 cm x 43.2 cm | 59 kg |
| SERIES 4500 | S2 LI6-EX | LI6 | 1040 | 2438 | 3048 | 31.8 cm x 18.1 cm x 43.2 cm | 58 kg |
| SERIES 5000 | 2 KS 33P | SPEC | 1837 | 4406 | 5508 | 39.2 cm x 21.1 cm x 63.0 cm | 94 kg |
| SERIES 5000 | 2 OS 33P | SPEC | 1955 | 4536 | 5670 | 39.2 cm x 21.1 cm x 63.0 cm | 100.5 kg |
| SERIES 5000 | 2 YS 27P | SPEC | 2190 | 4975 | 6219 | 35.6 cm x 22.9 cm x 80.3 cm | 111.5 kg |
| SERIES 5000 | 2 YS 31P | SPEC | 2527 | 5741 | 7176 | 39.4 cm x 22.9 cm x 80.3 cm | 129 kg |
| SERIES 5000 | 2 YS 62P | SPEC | 5054 | 11482 | 14352 | 69.5 cm x 22.9 cm x 80.3 cm | 258.5 kg |
| 4 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 5000 | 4 CS 17P | SPEC | 568 | 1393 | 1742 | 36.5 cm x 21.0 cm x 46.4 cm | 58 kg |
| SERIES 5000 | 4 KS 21P | SPEC | 1148 | 2754 | 3443 | 40.0 cm x 23.8 cm x 62.9 cm | 121 kg |
| SERIES 5000 | 4 KS 25P | SPEC | 1404 | 3305 | 4131 | 40.0 cm x 27.0 cm x 62.9 cm | 142.5 kg |
| SERIES 5000 | 4 KS 27P | SPEC | 1518 | 3580 | 4475 | 40.0 cm x 27.0 cm x 62.9 cm | 153.5 kg |
| 6 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S6 GC2 | GC2 | 210 | 547 | 684 | 25.9 cm x 18.1 cm x 27.9 cm | 28 kg |
| SERIES 4000 | S6 GC2-HC | GC2 | 230 | 625 | 781 | 25.9 cm x 18.1 cm x 27.9 cm | 31.5 kg |
| SERIES 4000 | S6 145 | GC2H | 250 | 710 | 888 | 25.9 cm x 18.1 cm x 29.0 cm | 32 kg |
| SERIES 4000 | S6 250 | SPEC | 281 | 799 | 998 | 29.8 cm x 18.1 cm x 28.6 cm | 40 kg |
| SERIES 4000 | S6 305 | SPEC | 305 | 878 | 1097 | 31.1 cm x 18.1 cm x 36.2 cm | 41 kg |
| SERIES 4000 | S6 LI6 | LI6 | 390 | 910 | 1137 | 31.8 cm x 18.1 cm x 42.5 cm | 51 kg |
| SERIES 4000 | S6 LI6-HC | LI6 | 445 | 1040 | 1299 | 31.8 cm x 18.1 cm x 42.5 cm | 55.5 kg |
| SERIES 4000 | S6 LI6-SC | LI6 | 487 | 1169 | 1462 | 31.8 cm x 18.1 cm x 42.5 cm | 56.5 kg |
| SERIES 4000 | 6 HHG 31P | SPEC | 344 | 1337 | 1671 | 52.7 cm x 20.3 cm x 30.2 cm | 56.5 kg |
| SERIES 4000 | 6 EHG 31P | SPEC | 410 | 1549 | 1936 | 52.7 cm x 20.3 cm x 32.4 cm | 60 kg |
| SERIES 4000 | 6 HHG 9D | SPEC | 344 | 1337 | 1671 | 52.7 cm x 22.2 cm x 25.4 cm | 56.5 kg |
| SERIES 4500 | S6 LI6-EX | LI6 | 371 | 871 | 1088 | 31.8 cm x 18.1 cm x 42.5 cm | 59 kg |
| SERIES 5000 | 6 CS 17P | SPEC | 568 | 1393 | 1742 | 55.9 cm x 21.0 cm x 46.4 cm | 100 kg |
| SERIES 5000 | 6 CS 21P | SPEC | 710 | 1742 | 2177 | 55.9 cm x 24.8 cm x 46.4 cm | 122.5 kg |
| SERIES 5000 | 6 CS 25P | SPEC | 853 | 2090 | 2612 | 55.9 cm x 28.6 cm x 46.4 cm | 144 kg |
| SERIES 5000 | 6 CS 27P | SPEC | 929 | 2264 | 2830 | 55.9 cm x 28.6 cm x 46.4 cm | 155 kg |



| FLOODED | MODEL | BCI | 20 HR | CCA @ -18°C (0°F) | MCA @ 0°C (32°F) | DIMENSIONS | WEIGHT |
|-------------|-------------|---------|-------|----------------------|---------------------|-----------------------------|---------|
| 8VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | 8 HHG 21P | SPEC | 230 | 1033 | 1291 | 54.0 cm x 18.7 cm x 28.3 cm | 53.5 kg |
| SERIES 4000 | 8 HHG 25P | SPEC | 275 | 1239 | 1549 | 62.2 cm x 18.7 cm x 29.2 cm | 59 kg |
| SERIES 4000 | 8 M 23P | SPEC | 240 | 891 | 1114 | 68.6 cm x 18.4 cm x 30.5 cm | 57.5 kg |
| SERIES 4000 | 8 HHG 29P | SPEC | 300 | 1446 | 1807 | 68.6 cm x 18.4 cm x 30.5 cm | 68 kg |
| SERIES 4000 | 8 HHG 31P | SPEC | 344 | 1337 | 1671 | 68.6 cm x 20.3 cm x 30.2 cm | 75.5 kg |
| SERIES 4000 | 8 EHG 31P | SPEC | 410 | 1549 | 1936 | 68.6 cm x 20.3 cm x 32.4 cm | 80.5 kg |
| SERIES 5000 | 8 CS 17P | SPEC | 568 | 1393 | 1742 | 71.8 cm x 21.0 cm x 46.4 cm | 133 kg |
| SERIES 5000 | 8 CS 25P | SPEC | 853 | 2090 | 2612 | 71.8 cm x 28.6 cm x 46.4 cm | 192 kg |
| SERIES 5000 | 8 CS 27P | SPEC | 929 | 2264 | 2830 | 71.8 cm x 28.6 cm x 46.4 cm | 207 kg |
| 12VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S12 24 | 24 | 85 | 550 | 690 | 27.9 cm x 17.1 cm x 23.8 cm | 21.5 kg |
| SERIES 4000 | S12 27 | 27 | 105 | 660 | 825 | 32.1 cm x 17.1 cm x 23.8 cm | 24.5 kg |
| SERIES 4000 | S12 31 | 31 | 130 | 620 | 775 | 33.0 cm x 17.1 cm x 24.1 cm | 29.5 kg |
| SERIES 4000 | I2 HHG 185P | 4D MOD | 185 | 713 | 891 | 52.7 cm x 22.2 cm x 25.4 cm | 55 kg |
| SERIES 4000 | S12 185 | 92I | 210 | 810 | 1013 | 39.1 cm x 17.8 cm x 36.5 cm | 61 kg |
| SERIES 4000 | I2 EHG 210P | 4DH | 210 | 778 | 972 | 52.7 cm x 22.2 cm x 31.4 cm | 62.5 kg |
| SERIES 4000 | I2 HHG 325P | 8D BOX | 325 | 1069 | 1337 | 55.2 cm x 33.7 cm x 28.7 cm | 90.5 kg |
| SERIES 4000 | I2 EHG 375P | 8D BOX | 375 | 1166 | 1458 | 55.2 cm x 33.7 cm x 31.0 cm | 104 kg |
| SERIES 4000 | I2 MD 325P | 2 x 27 | 325 | 1069 | 1337 | 47.0 cm x 38.3 cm x 28.1 cm | 90.5 kg |
| SERIES 4000 | I2 MD 375P | 2 x 27H | 375 | 1166 | 1458 | 47.0 cm x 38.3 cm x 31.9 cm | 104 kg |
| SERIES 5000 | I2 CS 11P | SPEC | 371 | 871 | 1088 | 55.9 cm x 28.6 cm x 46.4 cm | 123 kg |



| FLOODED | MODEL | BCI | 20 HR | CCA @ -18°C (0°F) | MCA @ 0°C (32°F) | DIMENSIONS | WEIGHT |
|-------------|------------------|------|-------|----------------------|---------------------|---------------------------|-----------|
| 2 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S2 LI6 | LI6 | 1169 | 2729 | 3411 | 12.5" x 7.13" x 17" | 120 Lbs |
| SERIES 4000 | S2 LI6-HC | LI6 | 1335 | 3119 | 3898 | 12.5" x 7.13" x 17" | 127 Lbs |
| SERIES 4000 | S2 LI6-SC | LI6 | 1503 | 3378 | 4223 | 12.5" x 7.13" x 17" | 130 Lbs |
| SERIES 4500 | S2 LI6-EX | LI6 | 1040 | 2438 | 3048 | 12.5" x 7.13" x 17" | 128 Lbs |
| SERIES 5000 | 2 KS 33P | SPEC | 1837 | 4406 | 5508 | 15.44" x 8.31" x 24.81" | 207 Lbs |
| SERIES 5000 | 2 OS 33P | SPEC | 1955 | 4536 | 5670 | 15.44" x 8.31" x 24.81" | 221.5 Lbs |
| SERIES 5000 | 2 YS 27P | SPEC | 2190 | 4975 | 6219 | 14" x 9" x 31.63" | 246 Lbs |
| SERIES 5000 | 2 YS 31P | SPEC | 2527 | 5741 | 7176 | 15.5" x 9" x 31.63" | 284.5 Lbs |
| SERIES 5000 | 2 YS 62P | SPEC | 5054 | 11482 | 14352 | 27.38" x 9" x 31.63" | 570 Lbs |
| 4 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 5000 | 4 CS 17P | SPEC | 568 | 1393 | 1742 | 14.38" x 8.25" x 18.25" | 128 Lbs |
| SERIES 5000 | 4 KS 21P | SPEC | 1148 | 2754 | 3443 | 15.75" x 9.38" x 24.75" | 267 Lbs |
| SERIES 5000 | 4 KS 25P | SPEC | 1404 | 3305 | 4131 | 15.75" x 10.63" x 24.75" | 314 Lbs |
| SERIES 5000 | 4 KS 27P | SPEC | 1518 | 3580 | 4475 | 15.75" x 10.63" x 24.75" | 338.5 Lbs |
| 6 VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S6 GC2 | GC2 | 210 | 547 | 684 | 10.19" x 7.13" x 11" | 61.5 Lbs |
| SERIES 4000 | S6 GC2-HC | GC2 | 230 | 625 | 781 | 10.19" x 7.13" x 11" | 69.5 Lbs |
| SERIES 4000 | S6 145 | GC2H | 250 | 710 | 888 | 10.19" x 7.13" x 11.40" | 70.5 Lbs |
| SERIES 4000 | S6 250 | SPEC | 281 | 799 | 998 | 11.75" x 7.13" x 11.25" | 88 Lbs |
| SERIES 4000 | S6 305 | SPEC | 305 | 878 | 1097 | 12.25" x 7.13" x 14.25" | 90.5 Lbs |
| SERIES 4000 | S6 LI6 | LI6 | 390 | 910 | 1137 | 12.5" x 7.13" x 16.75" | 112.5 Lbs |
| SERIES 4000 | S6 LI6-HC | LI6 | 445 | 1040 | 1299 | 12.5" x 7.13" x 16.75" | 122.5 Lbs |
| SERIES 4000 | S6 LI6-SC | LI6 | 487 | 1169 | 1462 | 12.5" x 7.13" x 16.75" | 124.5 Lbs |
| SERIES 4000 | 6 HHG 31P | SPEC | 344 | 1337 | 1671 | 20.75" x 8" x 11.88" | 124.5 Lbs |
| SERIES 4000 | 6 EHG 31P | SPEC | 410 | 1549 | 1936 | 20.75" x 8" x 12.75" | 132.5 Lbs |
| SERIES 4000 | 6 HHG 9D | SPEC | 344 | 1337 | 1671 | 20.75" x 8.75" x 10" | 124.5 Lbs |
| SERIES 4500 | S6 LI6-EX | LI6 | 371 | 871 | 1088 | 12.5" x 7.13" x 16.75" | 130 Lbs |
| SERIES 5000 | 6 CS 17P | SPEC | 568 | 1393 | 1742 | 22" x 8.25" x 18.25" | 220.5 Lbs |
| SERIES 5000 | 6 CS 21P | SPEC | 710 | 1742 | 2177 | 22" x 9.75" x 18.25" | 271 Lbs |
| SERIES 5000 | 6 CS 25P | SPEC | 853 | 2090 | 2612 | 22" x 11.25" x 18.25" | 317.5 Lbs |
| SERIES 5000 | 6 CS 27P | SPEC | 929 | 2264 | 2830 | 22" x 11.25" x 18.25" | 341.5 Lbs |



| FLOODED | MODEL | BCI | 20 HR | CCA @ -18°C (0°F) | MCA @ 0°C (32°F) | DIMENSIONS | WEIGHT |
|-------------|--------------------|---------|-------|----------------------|---------------------|---------------------------|-----------|
| 8VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | 8 HHG 21P | SPEC | 230 | 1033 | 1291 | 21.25" x 7.38" x 11.13" | 118 Lbs |
| SERIES 4000 | 8 HHG 25P | SPEC | 275 | 1239 | 1549 | 24.5" x 7.38" x 11.5" | 130 Lbs |
| SERIES 4000 | 8 M 23P | SPEC | 240 | 891 | 1114 | 27" x 7.25" x 12" | 127 Lbs |
| SERIES 4000 | 8 HHG 29P | SPEC | 300 | 1446 | 1807 | 27" x 7.25" x 12" | 150 Lbs |
| SERIES 4000 | 8 HHG 31P | SPEC | 344 | 1337 | 1671 | 27" x 8" x 11.88" | 167 Lbs |
| SERIES 4000 | 8 EHG 31P | SPEC | 410 | 1549 | 1936 | 27" x 8" x 12 3/4" | 178 Lbs |
| SERIES 5000 | 8 CS 17P | SPEC | 568 | 1393 | 1742 | 28.25" x 8.25" x 18.25" | 293 Lbs |
| SERIES 5000 | 8 CS 25P | SPEC | 853 | 2090 | 2612 | 28.25" x 11.25" x 18.25" | 423.5 Lbs |
| SERIES 5000 | 8 CS 27P | SPEC | 929 | 2264 | 2830 | 28.25" x 11.25" x 18.25" | 456 Lbs |
| 12VOLT | | | | | | L x W x H (incl terminal) | |
| SERIES 4000 | S12 24 | 24 | 85 | 550 | 690 | 11" x 6.75" x 9.38" | 47.5 Lbs |
| SERIES 4000 | S12 27 | 27 | 105 | 660 | 825 | 12.63" x 6.75" x 9.38" | 54 Lbs |
| SERIES 4000 | S12 31 | 31 | 130 | 620 | 775 | 13" x 6.75" x 9.50" | 65 Lbs |
| SERIES 4000 | I2 HHG 185P | 4D MOD | 185 | 713 | 891 | 20.75" x 8.75" x 10" | 121.5 Lbs |
| SERIES 4000 | S12 185 | 92I | 210 | 810 | 1013 | 15.38" x 7" x 14.38" | 134.5 Lbs |
| SERIES 4000 | I2 EHG 210P | 4DH | 210 | 778 | 972 | 20.75" x 8.75" x 12.38" | 138 Lbs |
| SERIES 4000 | I2 HHG 325P | 8D BOX | 325 | 1069 | 1337 | 21.75" x 13.25" x 11.31" | 199.5 Lbs |
| SERIES 4000 | I2 EHG 375P | 8D BOX | 375 | 1166 | 1458 | 21.75" x 13.25" x 12.19" | 229.5 Lbs |
| SERIES 4000 | I2 MD 325P | 2 x 27 | 325 | 1069 | 1337 | 18.50" x 15.06" x 11.06" | 199.5 Lbs |
| SERIES 4000 | I2 MD 375P | 2 x 27H | 375 | 1166 | 1458 | 18.50" x 15.06" x 12.56" | 229.5 Lbs |
| SERIES 5000 | I2 CS 11P | SPEC | 371 | 871 | 1088 | 22" x 11.25" x 18.25" | 271 Lbs |