




FLOODED		MODEL	BCI	20 HR	100 HR	TERMINAL	DIMENSIONS	WEIGHT	
2 VOLT								L x W x H (incl terminal)	
SERIES 4000	•	S2 L16	L16	1169	1344	LT	31.8 cm x 18.1 cm x 43.2 cm	54.5 kg	
SERIES 4000	•	S2 L16-HC	L16	1335	1535	LT	31.8 cm x 18.1 cm x 43.2 cm	57.5 kg	
SERIES 4000	•	S2 L16-SC	L16	1503	1728	LT	31.8 cm x 18.1 cm x 43.2 cm	59 kg	
SERIES 4500	•	S2 L16-EX	L16	1040	1342	LT	31.8 cm x 18.1 cm x 43.2 cm	58 kg	
SERIES 5000	•	2 KS 33P	SPEC	1837	2369	FLAG	39.2 cm x 21.1 cm x 63.0 cm	94 kg	
SERIES 5000	•	2 OS 33P	SPEC	1955	2522	FLAG	39.2 cm x 21.1 cm x 63.0 cm	100.5 kg	
SERIES 5000	•	2 YS 27P	SPEC	2190	2825	FLAG	35.6 cm x 22.9 cm x 80.3 cm	111.5 kg	
SERIES 5000	•	2 YS 31P	SPEC	2527	3260	FLAG	39.4 cm x 22.9 cm x 80.3 cm	129 kg	
SERIES 5000	•	2 YS 62P	SPEC	5054	6520	FLAG	69.5 cm x 22.9 cm x 80.3 cm	258.5 kg	
4 VOLT								L x W x H (incl terminal)	
SERIES 5000	•	4 CS 17P	SPEC	568	733	FLAG	36.5 cm x 21.0 cm x 46.4 cm	58 kg	
SERIES 5000	•	4 KS 21P	SPEC	1148	1481	FLAG	40.0 cm x 23.8 cm x 62.9 cm	121 kg	
SERIES 5000	•	4 KS 25P	SPEC	1404	1811	FLAG	40.0 cm x 27.0 cm x 62.9 cm	142.5 kg	
SERIES 5000	•	4 KS 27P	SPEC	1518	1959	FLAG	40.0 cm x 27.0 cm x 62.9 cm	153.5 kg	
6 VOLT								L x W x H (incl terminal)	
SERIES 4000	•	S6 GC2	GC2	210	269	DT	25.9 cm x 18.1 cm x 27.9 cm	28 kg	
SERIES 4000	•	S6 GC2-HC	GC2	241	308	DT	25.9 cm x 18.1 cm x 27.9 cm	31.5 kg	
SERIES 4000	•	S6 145	GC2H	250	320	DT	25.9 cm x 18.1 cm x 29.0 cm	32 kg	
SERIES 4000	•	S6 L16	L16	390	449	LT	31.8 cm x 18.1 cm x 42.5 cm	51 kg	
SERIES 4000	•	S6 L16-HC	L16	445	512	LT	31.8 cm x 18.1 cm x 42.5 cm	55.5 kg	
SERIES 4000	•	S6 L16-SC	L16	487	580	LT	31.8 cm x 18.1 cm x 42.5 cm	56.5 kg	
SERIES 4500	•	S6 L16-EX	L16	371	479	LT	31.8 cm x 18.1 cm x 42.5 cm	59 kg	
SERIES 5000	•	6 CS 17P	SPEC	568	733	FLAG	55.9 cm x 21.0 cm x 46.4 cm	100 kg	
SERIES 5000	•	6 CS 21P	SPEC	710	916	FLAG	55.9 cm x 24.8 cm x 46.4 cm	122.5 kg	
SERIES 5000	•	6 CS 25P	SPEC	853	1100	FLAG	55.9 cm x 28.6 cm x 46.4 cm	144 kg	
SERIES 5000	•	6 CS 27P	SPEC	929	1198	FLAG	55.9 cm x 28.6 cm x 46.4cm	155 kg	
8 VOLT								L x W x H (incl terminal)	
SERIES 5000	•	8 CS 17P	SPEC	568	733	FLAG	71.8 cm x 21.0 cm x 46.4 cm	133 kg	
SERIES 5000	•	8 CS 25P	SPEC	853	1100	FLAG	71.8 cm x 28.6 cm x 46.4 cm	192 kg	
SERIES 5000	•	8 CS 27P	SPEC	929	1198	FLAG	71.8 cm x 28.6 cm x 46.4 cm	207 kg	
12 VOLT								L x W x H (incl terminal)	
SERIES 4000		S12 24	24	85	106	DT	27.9 cm x 17.1 cm x 23.8 cm	21.5 kg	
SERIES 4000		S12 27	27	105	140	DT	32.1 cm x 17.1 cm x 23.8 cm	24.5 kg	
SERIES 4000		S12 31	31	130	173	DT	33.0 cm x 17.1 cm x 24.1 cm	29.5 kg	
SERIES 4000	•	S12 GC	GC12	155	206	UTL	33.3 cm x 18.2 cm x 27.4 cm	37.5 kg	
SERIES 4000	•	S12 185	921	210	279	DT	39.1 cm x 17.8 cm x 36.5 cm	52 kg	
SERIES 5000	•	12 CS 11P	SPEC	357	504	FLAG	55.9 cm x 28.6 cm x 46.4 cm	123 kg	

SERIES 4000 - 3 year full replacement  
 SERIES 4500 - 4 year full replacement  
 SERIES 5000 - 5 year full replacement



FLOODED		MODEL	BCI	20 HR	100 HR	TERMINAL	DIMENSIONS	WEIGHT	
2 VOLT								L x W x H (incl terminal)	
SERIES 4000	•	<b>S2 LI6</b>	LI6	1169	1344	LT	12.50" x 7.13" x 17"	120 Lbs	
SERIES 4000	•	<b>S2 LI6-HC</b>	LI6	1335	1535	LT	12.50" x 7.13" x 17"	127 Lbs	
SERIES 4000	•	<b>S2 LI6-SC</b>	LI6	1503	1728	LT	12.50" x 7.13" x 17"	130 Lbs	
SERIES 4500	•	<b>S2 LI6-EX</b>	LI6	1040	1342	LT	12.50" x 7.13" x 17"	128 Lbs	
SERIES 5000	•	<b>2 KS 33P</b>	SPEC	1837	2369	FLAG	15.44" x 8.31" x 24.81"	207 Lbs	
SERIES 5000	•	<b>2 OS 33P</b>	SPEC	1955	2522	FLAG	15.44" x 8.31" x 24.81"	221.5 Lbs	
SERIES 5000	•	<b>2 YS 27P</b>	SPEC	2190	2825	FLAG	14" x 9" x 31.63"	246 Lbs	
SERIES 5000	•	<b>2 YS 31P</b>	SPEC	2527	3260	FLAG	15.50" x 9" x 31.63"	284.5 Lbs	
SERIES 5000	•	<b>2 YS 62P</b>	SPEC	5054	6520	FLAG	27.38" x 9" x 31.63"	570 Lbs	
4 VOLT								L x W x H (incl terminal)	
SERIES 5000	•	<b>4 CS 17P</b>	SPEC	568	733	FLAG	14.38" x 8.25" x 18.25"	128 Lbs	
SERIES 5000	•	<b>4 KS 21P</b>	SPEC	1148	1481	FLAG	15.75" x 9.38" x 24.75"	267 Lbs	
SERIES 5000	•	<b>4 KS 25P</b>	SPEC	1404	1811	FLAG	15.75" x 10.63" x 24.75"	314 Lbs	
SERIES 5000	•	<b>4 KS 27P</b>	SPEC	1518	1959	FLAG	15.75" x 10.63" x 24.75"	338.5 Lbs	
6 VOLT								L x W x H (incl terminal)	
SERIES 4000	•	<b>S6 GC2</b>	GC2	210	269	DT	10.19" x 7.13" x 11"	61.5 Lbs	
SERIES 4000	•	<b>S6 GC2-HC</b>	GC2	241	308	DT	10.19" x 7.13" x 11"	69.5 Lbs	
SERIES 4000	•	<b>S6 145</b>	GC2H	250	320	DT	10.19" x 7.13" x 11.40"	79 Lbs	
SERIES 4000	•	<b>S6 LI6</b>	LI6	390	449	LT	12.50" x 7.13" x 16.75"	113 Lbs	
SERIES 4000	•	<b>S6 LI6-HC</b>	LI6	445	512	LT	12.50" x 7.13" x 16.75"	123 Lbs	
SERIES 4000	•	<b>S6 LI6-SC</b>	LI6	487	580	LT	12.50" x 7.13" x 16.75"	125 Lbs	
SERIES 4500	•	<b>S6 LI6-EX</b>	LI6	371	479	LT	12.50" x 7.13" x 16.75"	131 Lbs	
SERIES 5000	•	<b>6 CS 17P</b>	SPEC	568	733	FLAG	22" x 8.25" x 18.25"	220.5 Lbs	
SERIES 5000	•	<b>6 CS 21P</b>	SPEC	710	916	FLAG	22" x 9.75" x 18.25"	270 Lbs	
SERIES 5000	•	<b>6 CS 25P</b>	SPEC	853	1100	FLAG	22" x 11.25" x 18.25"	317.5 Lbs	
SERIES 5000	•	<b>6 CS 27P</b>	SPEC	929	1198	FLAG	22" x 11.25" x 18.25"	341.5 Lbs	
8 VOLT								L x W x H (incl terminal)	
SERIES 5000	•	<b>8 CS 17P</b>	SPEC	568	733	FLAG	28.25" x 8.25" x 18.25"	293 Lbs	
SERIES 5000	•	<b>8 CS 25P</b>	SPEC	853	1100	FLAG	28.25" x 11.25" x 18.25"	423.5 Lbs	
SERIES 5000	•	<b>8 CS 27P</b>	SPEC	929	1198	FLAG	28.25" x 11.25" x 18.25"	456 Lbs	
12 VOLT								L x W x H (incl terminal)	
SERIES 4000		<b>S12 24</b>	24	85	106	DT	11" x 6.75" x 9.38"	47.5 Lbs	
SERIES 4000		<b>S12 27</b>	27	105	140	DT	12.63" x 6.75" x 9.38"	54 Lbs	
SERIES 4000		<b>S12 31</b>	31	130	173	DT	13" x 6.75" x 9.50"	65 Lbs	
SERIES 4000	•	<b>S12 GC</b>	GC12	155	206	UTL	13.13" x 7.17" x 10.80"	82.5 Lbs	
SERIES 4000	•	<b>S12 185</b>	921	210	279	DT	15.38" x 7" x 14.38"	114.5 Lbs	
SERIES 5000	•	<b>12 CS 11P</b>	SPEC	357	504	FLAG	22" x 11.25" x 18.25"	271 Lbs	

SERIES 4000 - 3 year full replacement  
 SERIES 4500 - 4 year full replacement  
 SERIES 5000 - 5 year full replacement